

AMP-250 series 200W~250W Desk-Top Adapter

SINGLE OUTPUT



UNIVERSAL INPUT


Power Saving Standard Mode High Performance

DIMENSION

- L165x W67.4x H34.5mm(Max.)

AC inlet : IEC-320-C14 Type

Unit : mm
Tolerance : ±0.2mm



FEATURE

- 90 to 264 VAC universal input
- Low ripple & noise
- Short circuit protection
- Over voltage protection
- Power saving $\leq 0.21W$ at 110VAC/230VAC
- Power factor correction > 0.95 at full load

ENVIRONMENTAL

- Operating temperature: $0^{\circ}C \sim +40^{\circ}C$
- Operating humidity: 20% ~ 85%
- Storage temperature: $-40^{\circ}C \sim +70^{\circ}C$
- Storage humidity: 10% ~ 95%

GENERAL SPECIFICATION

- Efficiency 92% type at full load
- Hold- up time 8.3ms at full load, (100V)
- Inrush current 80A/230 VAC
- Withstand voltage 2500 VAC, input to Output
- MTBF 50,000 hours
- Burn-in 100% for all shipped units
- EMI requirements Meets conduction limits of
 - a) FCC Class B
 - b) CISPR Class B
- Safety requirements Approval
 - a) UL 62368
 - b) IEC 62368

Output Voltage/Current Rating Chart

Model Name	Output Wattage	Output Voltage	Output Current
AMP-200-24	200W	24V	8.33A
AMP-240-40	240W	40V	6.0A
AMP-250-20	250W	24V	10.41A



Safety application : $40^{\circ}C$ Ambient temperature

★ Meets the requirements of these agencies



威海電子股份有限公司
WEIHAI POWER ELECTRONICS CO.,LTD.

6F. -6, No.700, Jhongjheng Rd., Jhonghe Dist.,
New Taipei City 235, Taiwan (R.O.C.)
TEL: 886-2-82273718 FAX: 886-2-82273719
E-MAIL: sales@wpe.com.tw