

# Microcentrifuge

## M1324

Make Your Centrifugation Simple



### Highlights

#### Excellent and Efficient

- Unique heat dissipation material and duct design to enhance heat dissipation performance
- Double cooling system to ensure stable centrifugation of samples at the highest speed
- Running vibration amplitude  $\leq 1\mu\text{m}$  to maintain stable operation

#### Stable and Safe

- Standard aerosol-tight rotor with aerospace-grade aluminum alloy withstands high temperature sterilization and avoids biohazards
- Qualified ultrasonic non-destructive test, Schenck balancing test and extreme blasting test to protect personnel safety
- Real-time rotor dynamic balancing monitoring system and multiple-imbalance alarm functions guarantee safe operation

#### Intelligent and Quiet

- Dual noise control system with intelligent three-gear fan control, full load at maximum speed noise  $< 50\text{dB(A)}$
- Combination of touch screen and function keys provides quick and convenient setting and parameter use
- Use EPP foam material to reduce noise pollution

#### Simple and Practical

- Quick-lock rotor closes with only 1/6 turn for easy and secure sample handling
- 10 acceleration and deceleration ramps meet the centrifugation needs of different samples
- 48 custom programs enable immediate centrifuge operation in multiple scenarios
- Automatic lid opening design, easy and quick to take samples

Unique air duct design


Standard Aerosol-tight quick-lock rotor

4.3-inch touch screen

Combination of buttons and touch interaction



Aerosol-tight quick-lock rotor



Custom program storage



10 acceleration and deceleration ramps



## Technical Parameter

Parameters	Description
Max. Speed	15800rpm
Max. RCF	23444×g
Max.Capacity	2mL×24
Noise Level	<50dB(A)
ACC/DEC Ramps	10/10
Display	Touch screen
Program	48 set
Dimension (W*H*D)	262mm*282mm*385mm
Weight(with rotor)	~22kg



## Order Information

Model	Product Description
M1324	Ventilated Microcentrifuge (Rotor with Aerosol-tight quick- lock Lid)
M-F24QG	Aerosol-tight Lid , 24×1.5/2.0 mL tube quick- lock rotor
M-F24Q	24×1.5/2 mL tube quick- lock rotor
M-F24G	Aerosol-tight Lid, 24 ×1.5/2 mL tube rotor
M-F24	24×1.5/2 mL tube rotor
M-F4PCR	4 × PCR tube rotor
M-F18Kit	18 × Spin column rotor

## RWD Life Science Co.,Ltd

Add: 19-20/F, Building 7A, Shenzhen International Innovation Valley, Dashi 1<sup>st</sup>Road, Nanshan District, Shenzhen, Guangdong, P.R. China E-mail: [rwd@rwdstco.com](mailto:rwd@rwdstco.com)

## RWD Life Science Inc.

Tel: (858)900-5879 Support: [service@rwdls.com](mailto:service@rwdls.com) Web: [www.rwdstco.com](http://www.rwdstco.com)

