



# FiberWELD® DHc

Laser Mechanisms' FiberWELD® DHc is a compact material deposition head that is engineered for high duty cycle production applications with low to high power, fiber-delivered lasers. The head's advanced optical design permits wire to be fed directly into the beam path – coaxially to the beam and right into the center of the melt pool. This allows the additive or cladding process to have total directional independence. FiberWELD® DHc also delivers extended beam-on-time for 24/7 operation.

## Features

- For all fiber-delivered laser systems (Diode, Fiber, Disc) up to 8 kW
- Hot wire compliant
- Direct-cooled wire feed
- All optics are housed in sealed compartments to prevent contamination from process smoke and debris
- Temperature monitored optics
- Cover glass contamination monitoring/warning
- Cross-flow air knife
- Omnidirectional processing
- Direct-cooled, back-reflection protection



*Laser Mechanisms' compact FiberWELD® DHc is ideal for heavy deposition cladding and additive applications.*

- Quick and easy access to the cover slide (no tools required)
- Direct water-cooled nozzle
- Optional camera-based vision and process monitoring

## Specifications

Power Rating	up to 8 kW
Clear Aperture	44 mm
Collimator Focal Lengths	100 mm, 125 mm, 150 mm, 175 mm, 200 mm
Focal Length	300 mm
Wavelengths (Diode, Fiber, Disc)	900 - 1100 µm
Fiber Connections	QD (LLK-D, LCA), QBH (HLC-8), HLC-16
Wire Sizes	0.6 - 1.6 mm
Weight	~18 kg*

\*Base configuration. Weight will vary based on options added.

Specifications subject to change without notice.

長豐光學科技股份有限公司  
Laser Mechanisms Taiwan Ltd.

111052 台北市士林區承德路四段192-1號13樓  
13F., No. 192-1, Sec. 4, Chengde Rd., Shilin Dist.,  
Taipei City 111052, Taiwan  
E-mail: [info@lasermech.com.tw](mailto:info@lasermech.com.tw)  
TEL: +886-2-2881-3678  
FAX: +886-2-2881-3578



Website: [www.lasermech.com.tw](http://www.lasermech.com.tw)  
July 2023